

SURE B74-M352-F3

Camera Analog Full HD Bullet

Các Tính Năng Chính

- 1/2.9" 2.1 MP Sony Exmor CMOS
- Color : 0.1 Lux(50IRE) / 0.02 Lux(15IRE)
- Ngõ ra video AHD, TVI, 960H
- 1080p30/25, 720p30/25, 720p50/60, 960H
- Ống kính Megapixel 3.6mm
- Giảm nhiễu 3DNR
- Điều khiển OSD
- Bù sáng nền D-WDR/BLC/HLC
- True Day&Night (ICR)
- Khử sương mờ (De-Fog)
- Cấp bảo vệ kín IP66
- 63 IR LED khoảng cách ~45m



THÔNG SỐ KỸ THUẬT

Type	Bullet
Sensor	1/2.9" 2.1 MP Sony Exmor CMOS
Lens	Megapixel 3.6mm
View Angle	84°
Illuminator	63pcs 850nm IR LED
Video Output	HD-TVI, AHD, CVBS
Resolution	1080P25(30) / 720P25(30) / 960H

Min. Illumination	Color: 0.1 Lux(50IRE) / 0.02 Lux(15IRE) B/W: 0.08 Lux(50IRE) / 0.002 Lux(15IRE)
Frequency	NTSC/ PAL
Shutter	1/30(1/25) ~ 1/50Ksec
AGC	Mức (0~15)
ACE	N/A
Backlight	OFF/ BLC/ HSBLC/ D-WDR
Defog	OFF/ AUTO
Smart IR	OFF/ ON
Sense-Up	x2,x4,x6,x8,x10,x15,x20,x25,x30
Day & Night	AUTO/ COLOR/ B&W/ EXTERNAL
White Balance	ATW, AWCSET, INDOOR, OUTDOOR, MANUAL, AWB
Noise Reduction	OFF,LOW,MIDDLE,HIGH (2DNR + 3DNR)
Image Adjustment	SHARPNESS, MONITOR, LSC
Flip	OFF/H-MIRROR/V-MIRROR
Voltage	DC 12V(±10%)
Power Consumption	IR OFF : 150mA / IR ON : 700mA (MAX)
Dimension	77.7(W)x87.3(H)x280.3(L) mm
Weight	About 0.85kg
Operating Temperature	-10°C ~ +50°C
Operating Humidity	MAX 90% RH
Approval	KCC, FCC, CE, RoHS, IP66